


Shower chan. Linearis Infinity 90 L: 1000 mm, DN 40, Black, brushed





Article information

Item no.: 45202.10 GTIN: 4026092094259

Price group: 10

Advantages

- Channel profile made of 316 stainless steel
- Including Sound and settlement absorbers
- No flooding of the waterproofing level in the event of water build-up

Description

The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The channel profile made of 316 stainless steel can be extended straight or at three (30, 45 and 90 degree) angles. The drain body made of PP is equipped with sound and settlement absorbers. The channel contains a clip-on flange with factory-mounted waterproofing membrane to EN 1253-1 and DIN 18534-1-W3-I. The channel profile can be pushed in the lengthwise and transverse direction in the clip-on flange to level out construction tolerance. Including odour trap with 50 mm water seal. Open seepage water openings, without flooding of the waterproofing level in the event of backwater.

Variant

Water supply:	W3-I
Sealing water height:	50 mm
Discharge rate (l/s) with 10 mm backwater:	0,6
Discharge rate (l/s) with 20 mm backwater:	0,8

General characteristics

Nominal size (DN): 50 Outer diameter (OD): 50 mm

Dimensions

Net weight: 3,1 kg
Gross weight: 3,1 kg
Min. design height: 90 mm



Vertically adjustable:

Length:

Width:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Phickaging dimension:

Packaging dimension:

Ves

264 mm

111 mm

Packaging dimension:

Ves

464 mm

Vidth

Packaging dimension:

Ves

464 mm

Note of the control of the control

Tank/drain body

Outlet nominal size (OD): 50 mm
Outlet nominal size (DN): 50 mm
Material of drain body: PP
System: lateral

Coverage features

Type of cover: Stainless steel cover Cover material: 316 stainless steel

Width of cover: 45 mm
Length of cover: 1000 mm
Min. flooring height: 11 mm

Surface: Black brushed

Cover locking: placed

Load class: K 3 (EN 1253-1)

Max. flooring height: 25 mm Shape of upper section: square

Odour trap: with 50 mm water seal