



Ecoguss project drain DN 70, horiz., Variofix, Design cover





Article information

Item no.: 48378.53 GTIN: 4026092052907

Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Waterproofing layer on the drain body: Connection flange

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1

Nominal size (DN): 70 Outer diameter (OD): 78 mm

Dimensions

Net weight: 2,7 kg Gross weight: 3,46 kg

Vertical adjustment: vertically adjustable upper section

Packaging dimension: length



Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss System: lateral

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 120 mm
Length of cover: 120 mm
Min. flooring height: 10 mm
Surface: ground

Frame material: Stainless steel 14301

Cover locking: Lock & Lift Load class: L 15 (EN 1253-1)

Grating colour: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim length: 132 mm
Rim material: 132 mm
Max. flooring height: 24 mm

Upper section: adjustable in three dimensions

Shape of upper section: square
Upper section material: ABS
Odour trap: included