



## Ecoguss project drain DN 100, vert., Variofix, Design cover





## Article information

Item no.: 48411.53 GTIN: 4026092053911 Price group: 40

## **Advantages**

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

## Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant System: Waterproofing layer on the upper section:	125 Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm
General characteristics Standard: Nominal size (DN): Outer diameter (OD): Inlet max. scoring (DN):	EN 1253-1 100 110 mm Z-19.53-2414,Z-19.17-1719
Dimensions Net weight: Gross weight: Diameter:	2,58 kg 3,48 kg 135 mm



Vertical adjustment: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Number of outlets: Material of drain body: System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Min. flooring height: Surface: Frame material: Cover locking: Load class: Grating colour: Slip resistance class:

Rim length: Rim material: Max. flooring height: Upper section: Shape of upper section: Upper section material: Odour trap: vertically adjustable upper section 135 mm 135 mm length width height

1 Ecoguss vertical

Design cover Stainless steel 14301 silver 120 mm 120 mm 10 mm ground Stainless steel 14301 Lock & Lift L 15 (EN 1253-1) Kessel R9 according to DIN 51130; C according to DIN 51097 132 mm 132 mm 24 mm adjustable in three dimensions square ABS included