


## Backwater valve Staufix DN 90, Floor slab, tileable, Type 2



### Article information

Item no.: 730090.10X  
 GTIN: 4026092076323  
 Price group: 10

### Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

### Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

#### Variant

|                                         |     |
|-----------------------------------------|-----|
| Stainless steel flap as rat protection: | no  |
| Emergency closure:                      | yes |
| Mechanical backwater flaps:             | 2   |

#### General characteristics

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Colour:                 | black                                                           |
| Standard:               | EN 13564                                                        |
| Nominal size (DN):      | 90                                                              |
| Outer diameter (OD):    | 90 mm                                                           |
| Type of wastewater:     | without sewage                                                  |
| Installation situation: | floor slab installation                                         |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Backwater protection:   | Type 2                                                          |

#### Dimensions

|             |         |
|-------------|---------|
| Net weight: | 5,92 kg |
|-------------|---------|

|                                                        |                                     |
|--------------------------------------------------------|-------------------------------------|
| Gross weight:                                          | 8,5 kg                              |
| Groundwater resistant from lower edge of base section: | 3 mm                                |
| Cutout dimension, width:                               | 750 mm                              |
| Cutout dimension, length:                              | 750 mm                              |
| Vertical drop between inlet and outlet:                | 8 mm                                |
| Installation depth:                                    | 287 - 410 mm                        |
| Vertical adjustment:                                   | vertically adjustable upper section |
| Length:                                                | 444 mm                              |
| Width:                                                 | 444 mm                              |
| Packaging dimension:                                   | length                              |
| Packaging dimension:                                   | width                               |
| Packaging dimension:                                   | height                              |
| Coverage features                                      |                                     |
| Type of cover:                                         | tileable cover plate                |
| Cover material:                                        | Polymer                             |
| Width of cover:                                        | 366 mm                              |
| Length of cover:                                       | 366 mm                              |
| Cover locking:                                         | Lock & Lift                         |
| Load class:                                            | K 3 (EN 1253-1)                     |
| Tightness:                                             | surface water resistant             |
| Max. flooring height:                                  | 16 mm                               |