

Grease separator EasyClean free NS 2, Standard



Article information

Item no.: 93002.01 GTIN: 4026092060872 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant Disposal variant: Protection class motor: Sludge bucket: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901):	Standard no 2 no no manual with suction hose F3
General characteristics Material: Installation situation: Delivery state: purchasable by service partner:	PE free-standing installation Installation-ready (connection parts must be connected on site) No
Dimensions Net weight: Gross weight: Set-up area, length: Set-up area, width:	80 kg 95 kg 1736 mm 674 mm



Set-up area, height: Required access area, length: Required access area, width: Required access area, height: Packaging dimension: Packaging dimension: Packaging dimension:	1434 mm 1500 mm 674 mm 1434 mm length width height
Tank/drain body Distance pipe bottom outlet to tank bottom: Distance pipe bottom inlet to tank bottom: Outlet nominal size (OD): Outlet nominal size (DN): Inlet nominal size (DN): Inlet nominal size (DN): Connection inlet/outlet sockets:	985 mm 1055 mm 110 mm 100 mm 110 mm 100 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features Type of cover: Cover material: Colour of cover: Cover locking: Tightness:	Cover Polymer violet Quick-release closure odour-tight
Wastewater contents Separator contents: Total volume: Hose: Storage quantity of light liquid:	400 l 600 l 200 l 100 l
Control Control unit:	ΠΟ