

Grease separator EasyClean free NS 4, Standard, Ref. in., Insp. Win., SC



Article information

Item no.: 93004.32 GTIN: 4026092063446 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	yes
Nominal size (NS):	4
SonicControl:	Ves
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3
General characteristics	
Material:	PE
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be
· · · / · · · ·	connected on site)
purchasable by service partner:	No
, , ,	
Dimensions	
Net weight:	112,5 kg
Gross weight:	142,5 kg
Set-up area, length:	2116 mm



Set-up area, width: Set-up area, height: Required access area, length: Required access area, width: Required access area, height: Packaging dimension: Packaging dimension: Packaging dimension:	680 mm 1432 mm 1880 mm 680 mm 1432 mm length width height
Tank/drain body Distance pipe bottom outlet to tank bottom: Distance pipe bottom inlet to tank bottom: Outlet nominal size (OD): Outlet nominal size (DN): Inlet nominal size (DN): Inlet nominal size (DN): Connection inlet/outlet sockets:	985 mm 1055 mm 110 mm 100 mm 110 mm 100 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features Type of cover: Cover material: Colour of cover: Cover locking: Tightness:	Cover Polymer violet Quick-release closure odour-tight
Wastewater contents Separator contents: Total volume: Hose: Storage quantity of light liquid:	400 l 800 l 400 l 160 l
Control Control unit:	no