

Grease separator EasyClean free NS 7, Standard, SonicControl



Article information

Item no.: 93007.02 GTIN: 4026092061480 Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant Disposal variant: Protection class motor: Sludge bucket: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901):	Standard no no 7 yes no manual with suction hose F3
General characteristics Material: Installation situation: Delivery state: purchasable by service partner:	PE free-standing installation Installation-ready (connection parts must be connected on site) No
Dimensions Net weight: Gross weight: Set-up area, length: Set-up area, width:	157,5 kg 190,5 kg 2147 mm 948 mm



Set-up area, height:	1653 mm
Required access area, length:	1910 mm
Required access area, width:	948 mm
Required access area, height:	1653 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
	noight
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150 mm
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	150 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	650 l
Total volume:	1350 l
Hose:	700 l
Storage quantity of light liquid:	280 l
Control	
Control unit:	no