

## Grease separator EasyClean free NS 7, Standard, Inspection window, SC



### Article information

Item no.: 93007.22  
 GTIN: 4026092063354  
 Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

Disposal variant:	Standard
Protection class motor:	no
Sludge bucket:	yes
Nominal size (NS):	7
SonicControl:	yes
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3

#### General characteristics

Material:	PE
Installation situation:	free-standing installation
Delivery state:	Installation-ready (connection parts must be connected on site)
purchasable by service partner:	No

#### Dimensions

Net weight:	16,5 kg
Gross weight:	193,5 kg
Set-up area, length:	2147 mm

Set-up area, width:	948 mm
Set-up area, height:	1653 mm
Required access area, length:	1910 mm
Required access area, width:	948 mm
Required access area, height:	1653 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	1185 mm
Distance pipe bottom inlet to tank bottom:	1255 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150 mm
Inlet nominal size (DN):	160 mm
Inlet nominal size (DN):	150 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Cover locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	650 l
Total volume:	1350 l
Hose:	700 l
Storage quantity of light liquid:	280 l
Control	
Control unit:	no