

## Grease separator EasyClean free NS 10, Standard, SonicControl



## **Article information**

Item no.: 93010.02 GTIN: 4026092061497 Price group: 60

## **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:

Protection class motor:

Sludge bucket:

Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

Standard

no

yes

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

purchasable by service partner: No

**Dimensions** 

Net weight: 195,5 kg
Gross weight: 238,5 kg
Set-up area, length: 2822 mm
Set-up area, width: 951 mm



Set-up area, height:

Required access area, length:

Required access area, width:

Sequired access area, width:

Sequired access area, height:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Neight

Sequired access area, height:

Sequired access area, width:

Sequired access area, width:

Sequired access area, width:

Sequired access area, height:

Se

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (DN):

Inlet nominal size (DN):

150 mm

Inlet nominal size (DN):

150 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: violet

Cover locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 900 l
Total volume: 1900 l
Hose: 1000 l
Storage quantity of light liquid: 400 l

Control

Control unit: