

## Grease separator EasyClean free NS 10, Standard, Refill inlet



### Article information

Item no.: 93010.11  
GTIN: 4026092063217  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

|   |                          |
|---|--------------------------|
| Disposal variant:                         | Standard                 |
| Protection class motor:                   | no                       |
| Sludge bucket:                            | no                       |
| Nominal size (NS):                        | 10                       |
| SonicControl:                             | no                       |
| Refill inlet in accordance with DIN 1988: | yes                      |
| Type of disposal:                         | manual with suction hose |
| Load-bearing capacity (DIN 19901):        | F3                       |

#### General characteristics

|                                 |   |
|---------------------------------|---|
| Material:                       | PE  |
| Installation situation:         | free-standing installation                                      |
| Delivery state:                 | Installation-ready (connection parts must be connected on site) |
| purchasable by service partner: | No  |

#### Dimensions

|                      |         |
|----------------------|---------|
| Net weight:          | 191 kg  |
| Gross weight:        | 234 kg  |
| Set-up area, length: | 2822 mm |
| Set-up area, width:  | 951 mm  |

|   |   |
|---|---|
| Set-up area, height:                        | 1653 mm   |
| Required access area, length:               | 2590 mm   |
| Required access area, width:                | 951 mm  |
| Required access area, height:               | 1653 mm   |
| Packaging dimension:                        | length  |
| Packaging dimension:                        | width   |
| Packaging dimension:                        | height  |
| Tank/drain body                             |   |
| Distance pipe bottom outlet to tank bottom: | 1185 mm   |
| Distance pipe bottom inlet to tank bottom:  | 1255 mm   |
| Outlet nominal size (OD):                   | 160 mm  |
| Outlet nominal size (DN):                   | 150 mm  |
| Inlet nominal size (DN):                    | 160 mm  |
| Inlet nominal size (DN):                    | 150 mm  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Coverage features                           |   |
| Type of cover:                              | Cover   |
| Cover material:                             | Polymer   |
| Colour of cover:                            | violet  |
| Cover locking:                              | Quick-release closure   |
| Tightness:                                  | odour-tight   |
| Wastewater contents                         |   |
| Separator contents:                         | 900 l   |
| Total volume:                               | 1900 l  |
| Hose:                                       | 1000 l  |
| Storage quantity of light liquid:           | 400 l   |
| Control                                     |   |
| Control unit:                               | no  |