

Replacement pump KTP/SPZ 1000 230 V, cable length 5 m



Article information

Item no.: 28351

GTIN: 4026092038420

Price group: 90

Description

Replacement pump with macerator for wastewater with sewage

Variant

Pump control: Control unit

General characteristics

Standard: EN 12050-1 Type of wastewater: with sewage

Dimensions

Net weight: 10,29 kg Gross weight: 10,62 kg Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device

Pump: SPZ 1000 Connection type: coded plug Operating voltage: 230 V 50 Hz Mains frequency: Protection class: F Insulation class: Cos phi - power factor: 0,97

IP 68 (3m/48h) Protection class (pump): Temperature monitoring: integrated 35°C

Max. temperature (permanent) of conveyed

material:

Max. pumping height: 10 m

Speed: 2800 U/min Power P1: 1,2 kW Power P2: 0,7 kW Operating mode: S3 - 50 %



Type of pump connection cable: H07RN-F 3G 1.5 mm²

Impeller type: Macerator

Length of mains cable for pump: 5 m Rated current: 5,2 A

Control

Operating voltage: 230 V Connection type: coded plug

Type of fuse required (electrical protection): Fuse protection through control unit 230 V