

Submers. pump Aquadive GTF 1700 res., without float switch, 10 m, 230 V

Article information

Item no.: 28782C
GTIN: 4026092113691
Price group: 20

Description

Submersible pump Aquadive GTF1700, resistant, without float switch, 10m

The submersible pump for maximum operational safety, with longitudinally watertight moulded connection line and removable intake cage.

Variant

Resistant: Resistant to waste water containing salt, softener and condensate
Pump control: without float switch

General characteristics

Material: Polymer, Stainless steel
Standard: EN 12050-2
Type of wastewater: without sewage
Cable length: 10 m

Dimensions

Length: 240 mm
Width: 200 mm
Height: 377 mm

Tank/drain body

Pressure pipe connection: R 1 ¼"

Pumping device

Pump: GTF 1700
Weight, pump: 13,9 kg
Connection type: coded plug
Operating voltage: 230 V
Protection class: I
Insulation class: F
Cos phi - power factor: 0,97
Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 40 °C

| | |
|--|--------------------------------|
| Hot water resistance for a short time (2 min): | 80 °C |
| Max. pumping height: | 13 m |
| Speed: | 2850 U/min |
| Power P1: | 1,6 kW |
| Power P2: | 1 kW |
| Operating mode: | S3 - 50 % |
| Type of pump connection cable: | H07RN-F 3G 1.5 mm ² |
| Impeller type: | Multi-vane impeller |
| Free passage: | 30 mm |
| Type of fuse required (pump): | C 16 A |
| Length of mains cable for pump: | 10 m |
| Rated current: | 7,3 A |
| Control | |
| Operating voltage: | 230 V |
| Connection type: | coded plug |
| Mains frequency: | 50 Hz |