


Submersible pump Aquadive GTF1000 resistant, with float switch, 10 m



Article information

Item no.: 28860C
GTIN: 4026092093771
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Submersible pump for faecal-free wastewater

Variant

Resistant:

Resistant to waste water containing salt, softener and condensate

Pump control:

Float switch

General characteristics

Type of wastewater:

without sewage

Dimensions

Net weight:

10 kg

Gross weight:

10,5 kg

Length:

195 mm

Width:

195 mm

Height:

290 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device

| | |
|--|--------------------------------|
| Pump: | GTF 1000 resistant |
| Weight, pump: | 10 kg |
| Connection type: | coded plug |
| Operating voltage: | 230 V |
| Protection class: | I |
| Insulation class: | F |
| Protection class (pump): | IP 68 (3m) |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Hot water resistance for a short time (2 min): | 80 °C |
| Max. pumping height: | 10 m |
| Speed: | 2700 U/min |
| Power P1: | 1,3 kW |
| Power P2: | 0,75 kW |
| Operating mode: | S3 - 50 % |
| Type of pump connection cable: | H07RN-F 3G 1.5 mm ² |
| Impeller type: | Multi-vane impeller |
| Free passage: | 10 mm |
| Type of fuse required (pump): | C 16 A |
| Length of mains cable for pump: | 10 m |
| Rated current: | 5,6 A |
| Control | |
| Type of level measurement: | mechanical |
| Mains frequency: | 50 Hz |
| Connection type: | coded plug |