

Submers. pump Aquadive GTF 1700 resitant, with float switch, 10 m, 230 V

Article information

Item no.: 28882C
GTIN: 4026092113684
Price group: 20

Description

Submersible pump Aquadive GTF1700, resistant, with float switch, 10m

The submersible pump for maximum operational safety, with longitudinally watertight moulded connection line and removable intake cage

Variant

Resistant:	Resistant to waste water containing salt, softener and condensate
Pump control:	Float switch

General characteristics

Material:	Polymer, Stainless steel
Standard:	EN 12050-2
Type of wastewater:	without sewage
Cable length:	10 m

Dimensions

Length:	240 mm
Width:	200 mm
Height:	377 mm

Tank/drain body

Pressure pipe connection:	R 1 ¼ "
---------------------------	---------

Pumping device

Pump:	GTF 1700
Weight, pump:	13,9 kg
Connection type:	coded plug
Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C

Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	13 m
Speed:	2850 U/min
Power P1:	1,6 kW
Power P2:	1 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	30 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	7,3 A
Control	
Operating voltage:	230 V
Connection type:	coded plug
Mains frequency:	50 Hz