

The Superflat bathroom drain glued flange, DN 50, tileable



Article information

Item no.: 42701.95 GTIN: 4026092029664 Price group: 10

Advantages

- Movable outlet socket
- Lip seal fixed on the drain body
- Side inlet via odour trap

Description

The Superflat bathroom drain is suitable for indoor floor drainage. The drain made of PP is equipped with a secure, reliably installed seal as well as a removable odour trap.

Variant Sealing water height: Discharge rate (l/s) with 20 mm threshold:	30 mm 0,8
General characteristics Nominal size (DN): Outer diameter (OD): Odour trap:	50 50 mm included
Dimensions Vertical adjustment: Net weight: Gross weight: Cutout dimension, width: Cutout dimension, length: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:	25 - 90 mm 0,93 kg 1,17 kg 350 mm 350 mm vertically adjustable upper section 332 mm 332 mm length width height
Tank/drain body Number of outlets: Inlet nominal size (DN): Number of inlets: Material of drain body:	1 40 mm 1 PP



Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Frame material: Locking: Load class: Rim width: Rim length: Upper section material:

tileable cover plate tileable selectable 110 mm 110 mm Stainless steel 14301 placed K 3 (EN 1253-1) 110 mm 110 mm PP