

Practicus basement drain DN 100, horiz., Black slotted grating



Article information

Item no.: 45110.40
 GTIN: 4026092032978
 Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:	no
Discharge rate (l/s) with 10 mm threshold:	1
Discharge rate (l/s) with 20 mm threshold:	1,6

General characteristics

Standard:	EN 1253-2
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Odour trap:	included

Dimensions

Vertical adjustment:	20 - 76 mm
Net weight:	1,14 kg
Gross weight:	1,2 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	220 mm
Installation depth:	152 - 208 mm
Type of height adjustability:	vertically adjustable upper section
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Number of outlets:	1
Material of drain body:	PP
Socket version:	lateral

Coverage features

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	138 mm
Height of cover:	16 mm
Length of cover:	138 mm
Frame material:	Polymer
Locking:	screwed
Load class:	K 3 (EN 1253-1)
Rim width:	150 mm
Rim length:	150 mm
Shape of upper section:	square
Upper section material:	Polymer
Contents of sludge trap:	no