

Practicus basement drain DN 100, horiz., Black slotted grating



Article information

Item no.: 45110.40 GTIN: 4026092032978

Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap: no
Discharge rate (l/s) with 10 mm backwater: 1
Discharge rate (l/s) with 20 mm backwater: 1,6

General characteristics

Standard: EN 1253-2 Nominal size (DN): 100 Outer diameter (OD): 110 mm

Dimensions

Vertical adjustment:20 - 76 mmNet weight:1,14 kgGross weight:1,2 kgCutout dimension, width:180 mmCutout dimension, length:220 mmInstallation depth:152 - 208 mm

Vertical adjustment: vertically adjustable upper section

Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: PP
System: lateral

Coverage features

Type of cover: Slotted cover



Cover material:

Colour of cover:

black

Width of cover:

138 mm

Height of cover:

16 mm

Length of cover:

138 mm

Frame material:

Polymer

Cover locking:

Polymer

Load class: K 3 (EN 1253-1)

Rim length: 150 mm
Rim material: 150 mm
Shape of upper section: square
Upper section material: Polymer
Contents of sludge trap: no
Odour trap: included