


Shower chan. Linearis Infinity 60 L: 1200 mm, DN 40, Black, br., Megastop





Article information

Item no.: 45302.12 GTIN: 4026092094327 Price group: 10

Advantages

- Channel profile made of 316 stainless steel
- Including Sound and settlement absorbers
- No flooding of the waterproofing level in the event of water build-up

Description

The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The channel profile made of 316 stainless steel can be extended straight or at three (30, 45 and 90 degree) angles. The drain body made of PP is equipped with sound and settlement absorbers. These reduce operating noise and can compensate for subsidence in the floor structure. The channel contains a clip-on flange with a factory-mounted waterproofing membrane according to DIN EN 1253-1 and DIN 18534-1-W3-I. The channel profile can be pushed in the lengthwise and transverse direction in the clip-on flange to compensate for construction tolerances. Including Megastop mechanical odour trap with water seal. Open seepage water openings, without flooding of the waterproofing level in the event of build-up.

Variant

Water exposure class in accordance to DIN	W3-I
18534-1 (up to and including):	
Discharge rate (l/s) with 10 mm threshold:	0,2
Discharge rate (l/s) with 20 mm threshold:	0,4
General characteristics	
Nominal size (DN):	40



Dimensions Net weight: Gross weight: Min. design height: Vertically adjustable: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Outlet nominal size (OD): Outlet nominal size (DN): Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Width of cover: Length of cover: Min. flooring height: Surface: Locking: Load class: Max. flooring height: Shape of upper section:

Megastop

3,45 kg 3,45 kg 60 mm yes 264 mm 111 mm length width height 40 mm 40 mm PP lateral

Stainless steel cover 316 stainless steel 45 mm 1200 mm 11 mm Black brushed placed K 3 (EN 1253-1) 25 mm square