

Scada wall drain w/cov, SST, 17 mm, fixed w/prf membrn



Article information

Item no.: 48000.04M GTIN: 4026092079140 Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory
- Alternative odour trap Multistop

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant Lighting:	without
Waterproofing layer on the drain body:	Factory-fitted sealing collar (WaD) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	22 mm
Discharge rate (l/s) with 20 mm threshold:	0,5
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	58 mm
Odour trap:	included
Dimensions	
Net weight:	2,29 kg
Gross weight:	2,45 kg
Length:	362 mm
Width:	195 mm
Height:	353 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS



Coverage features Type of cover: Cover material: Colour of cover: Height of cover: Length of cover: Min. flooring height: Frame material: Locking: Grating design: Max. flooring height: Shape of upper section: Upper section material:

Scada drain cover Stainless steel 14301 silver 67 mm 312 mm 22 mm ABS inserted Standard 67 26 mm square ABS