


## Linearis Comfort upper section L: 1150 mm, System 125, WaD, K 3



### Article information

Item no.: 48932M  
 GTIN: 4026092079089  
 Price group: 10

### Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

### Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

|  |  |
|--|--|
| Variant  |  |
| System:  | 125  |
| Seepage opening:   | open   |
| Waterproofing layer on the upper section:                                | Factory-fitted sealing collar (WaD) according to DIN 18534 |
| Water exposure class in accordance to DIN 18534-1 (up to and including): | W3-I   |
| Sealing water height:  | 50 mm  |
| Discharge rate (l/s) with 10 mm threshold:                               | 1,1  |
| Discharge rate (l/s) without threshold:                                  | 1 mm   |
| General characteristics  |  |
| Nominal size (DN):   | 125  |
| Outer diameter (OD):   | 125 mm   |
| Odour trap:  | included   |
| Dimensions   |  |
| Net weight:  | 4,55 kg  |
| Gross weight:  | 5,26 kg  |
| Outer dimension, length:   | 1215 mm  |
| Installation depth:  | 80 - 140 mm  |
| Width:   | 243 mm   |
| Height:  | 107 mm   |
| Packaging dimension:   | length   |
| Packaging dimension:   | width  |
| Packaging dimension:   | height   |

**Coverage features**

|                         |                       |
|-------------------------|-----------------------|
| Type of cover:          | Stainless steel cover |
| Cover material:         | Stainless steel 14301 |
| Colour of cover:        | silver                |
| Surface:                | Brushed SST           |
| Frame material:         | Stainless steel 14301 |
| Locking:                | lockable              |
| Load class:             | K 3 (EN 1253-1)       |
| Grating design:         | optionally tileable   |
| Rim width:              | 66 mm                 |
| Rim length:             | 1150 mm               |
| Shape of upper section: | square                |
| Upper section material: | ABS                   |