


Box Channel Ferrofix glued flange H: 6mm, 200x550mm



Article information

Item no.: 6220050
 GTIN: 4026092098721
 Price group: 80

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix box channel made of stainless steel with a material thickness of 1.5 mm (pickled in the immersion bath) is equipped with ground crosspieces, longitudinal and transverse gradients, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (6 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is also suitable for connecting waterproofing.

Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

General characteristics

Nominal size (DN): 125
 Outer diameter (OD): 125 mm
 Glued flange height: 6 mm

Dimensions

Length: 550 mm
 Width: 200 mm
 Height: 60 mm

Coverage features

Type of cover: Slotted cover
 Colour of cover: silver
 Locking: placed

Load class:	L 15 (EN 1253-1)
Slip resistance class:	R12 according to DIN 51130; C according to DIN 51097
Upper section material:	Stainless steel 14301