


## Floor Tray Ferrofix glued flange H: 6mm, 500x500mm



### Article information

Item no.: 6250050  
GTIN: 4026092099322  
Price group: 80

### Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

### Description

The Ferrofix floor tray made of stainless steel with a material thickness of 1.5 mm (pickled in the immersion bath) is equipped with ground crosspieces, longitudinal and transverse gradients, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (6 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is also suitable for connecting waterproofing.

#### Variant

Waterproofing layer on the upper section: Adhesive flange (suitable for moisture barriers)

#### General characteristics

Nominal size (DN): 125  
Outer diameter (OD): 125 mm  
Glued flange height: 6 mm

#### Dimensions

Net weight: 13,2 kg  
Gross weight: 13,2 kg  
Length: 500 mm  
Width: 500 mm  
Height: 60 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

Coverage features

Type of cover:

Colour of cover:

Locking:

Load class:

Slip resistance class:

Upper section material:

Slotted cover

silver

placed

L 15 (EN 1253-1)

R12 according to DIN 51130; C according to DIN 51097

Stainless steel 14301