


# Floor Tray Ferrofix glued flange H: 6mm, 800x800mm





## Article information

Item no.: 6280800 GTIN: 4026092099353 Price group: 80

### **Advantages**

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

# Description

The Ferrofix floor tray made of stainless steel with a material thickness of 1.5 mm (pickled in the immersion bath) is equipped with ground crosspieces, longitudinal and transverse gradients, feet for height adjustment and stainless steel outlet nozzles The channel profile is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim (6 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is also suitable for connecting waterproofing.

#### Variant

Waterproofing layer on the upper section:

General characteristics Nominal size (DN): Outer diameter (OD): Glued flange height:

Dimensions Length: Width: Height:

Coverage features Type of cover: Colour of cover: Locking: Load class: Adhesive flange (suitable for moisture barriers)

Slotted cover silver placed L 15 (EN 1253-1)

125

125 mm

800 mm

800 mm

60 mm

6 mm



Slip resistance class:

Upper section material:

R12 according to DIN 51130; C according to DIN 51097 Stainless steel 14301