

Yard drain Sys 200, horizontal, slot grat., A 15



Article information

Item no.: 67020.30
GTIN: 4026092003787
Price group: 10

Description

The polymer yard drain is used for point drainage and is equipped with a lip seal as well as a temporary protective cover.

Variant

| | |
|--|-----|
| System: | 200 |
| Discharge rate (l/s) with 20 mm threshold: | 4,5 |

General characteristics

| | |
|----------------------|--------|
| Standard: | EN 752 |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 mm |
| Odour trap: | no |

Dimensions

| | |
|----------------------|-------------|
| Vertical adjustment: | 40 - 150 mm |
| Net weight: | 3,09 kg |
| Gross weight: | 3,48 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-------------------------|---------|
| Number of outlets: | 1 |
| Material of drain body: | Polymer |
| Socket version: | lateral |

Coverage features

| | |
|------------------|---------------------|
| Type of cover: | Round slotted cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Width of cover: | 300 mm |
| Length of cover: | 300 mm |
| Surface: | EDM |

| | |
|-------------------------|---------------|
| Frame material: | Polymer |
| Locking: | placed |
| Load class: | A 15 (EN 124) |
| Rim width: | 300 mm |
| Rim length: | 300 mm |
| Shape of upper section: | square |
| Upper section material: | Polymer |