

Replacement pump GTF 1250 w. float switch, Aqualift S 100/200, 5m



Article information

Item no.: 680978
 GTIN: 4026092095911
 Price group: 90

Description

Replacement pump with float switch for faecal-free wastewater.

Variant	
Pump control:	Float switch
General characteristics	
Type of wastewater:	without sewage
Dimensions	
Net weight:	10,5 kg
Gross weight:	10,5 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	GTF 1250
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Mains frequency:	50 Hz
Protection class (pump):	IP 68 (3m)
Max. temperature (permanent) of conveyed material:	40 °C
Max. pumping height:	11 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,8 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	5 m

Rated current:	5,4 A
Control	
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A