

## Grease separator EasyClean free NS 7, Direct, Insp. window, SonicControl



### Article information

Item no.: 93007.22/D  
 GTIN: 4026092063651  
 Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|   |                     |
|---|---------------------|
| Disposal variant:                         | Direct              |
| Protection class motor:                   | no                  |
| Sludge bucket:                            | yes                 |
| Nominal size (NS):                        | 7                   |
| SonicControl:                             | yes                 |
| Disposal system:                          | Disposal connection |
| Refill inlet in accordance with DIN 1988: | no                  |
| Type of disposal:                         | manual              |
| Load-bearing capacity (DIN 19901):        | F3                  |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Standard:               | EN 1825   |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:      | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

#### Dimensions

|                               |         |
|-------------------------------|---------|
| Net weight:                   | 161 kg  |
| Gross weight:                 | 194 kg  |
| Set-up area, width:           | 970 mm  |
| Set-up area, height:          | 1653 mm |
| Set-up area, length:          | 2147 mm |
| Required access area, width:  | 940 mm  |
| Required access area, height: | 1653 mm |
| Required access area, length: | 1910 mm |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |
| Packaging dimension:          | length  |

#### Tank/drain body

|   |   |
|---|---|
| Nominal pressure (PN):                      | 10  |
| Pressure pipe connection (DN):              | 65  |
| Pressure pipe connection (OD):              | 75 mm   |
| Distance pipe bottom outlet to tank bottom: | 1185 mm   |
| Distance pipe bottom inlet to tank bottom:  | 1255 mm   |
| Outlet nominal size (OD):                   | 160 mm  |
| Outlet nominal size (DN):                   | 150   |
| Inlet nominal size (DN):                    | 160 mm  |
| Inlet nominal size (DN):                    | 150   |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Servicing opening:                          | 420 mm  |

#### Coverage features

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Cover locking:   | Quick-release closure |
| Tightness:       | odour-tight           |

#### Wastewater contents

|                                   |        |
|-----------------------------------|--------|
| Separator contents:               | 650 l  |
| Total volume:                     | 1350 l |
| Hose:                             | 700 l  |
| Storage quantity of light liquid: | 280 l  |

#### Control

|                                       |    |
|---------------------------------------|----|
| Max. permissible switching frequency: | no |
|---------------------------------------|----|