

Grease separator EasyClean free NS 50, Direct

Article information

Item no.: 93050.01/D GTIN: 4026092103807 Price group: 60

Advantages

- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

Variant

Disposal variant: Direct Shredder-Mix-System: no Inspection window: no Nominal size (NS): 50 SonicControl: no Refill inlet in accordance with DIN 1988: no manual Type of disposal: Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE Standard: EN 1825

Delivery state: Installation-ready (connection parts must be

connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle

connection

Dimensions

Gross weight: 820 kg
Set-up area, length: 6680 mm
Set-up area, width: 1800 mm
Set-up area, height: 1882 mm
Required access area, length: 6200 mm



Required access area, width:

Required access area, height:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Neight

Tank/drain body

Nominal pressure (PN): 10 65 Pressure pipe connection (DN): Pressure pipe connection (OD): 75 mm Distance pipe bottom outlet to tank bottom: 1350 mm Distance pipe bottom inlet to tank bottom: 1420 mm Outlet nominal size (OD): 250 mm Outlet nominal size (DN): 250 mm Inlet nominal size (OD): 250 mm Inlet nominal size (DN): 250 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 6200 l
Total volume: 11200 l
Contents of sludge trap: 5000 l
Storage quantity of grease: 2240 l

Control

Control unit: no