

Grease separator EasyClean free Basic, NS 10, rt, Insp wind, Ref inlet



Article information

Item no.: 94010.32R
GTIN: 4026092083956
Price group: 60

Advantages

- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|--------------------------|
| Direction of flow: | right |
| Disposal variant: | Standard |
| Inspection window: | yes |
| Nominal size (NS): | 10 |
| Refill inlet in accordance with DIN 1988: | yes |
| Type of disposal: | manual with suction hose |
| Sampling device: | no |
| Load-bearing capacity (DIN 19901): | F3 |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Installation situation: | free-standing installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|-------------------------------|---------|
| Net weight: | 170 kg |
| Gross weight: | 205 kg |
| Set-up area, length: | 2610 mm |
| Set-up area, width: | 1080 mm |
| Set-up area, height: | 1670 mm |
| Required access area, length: | 2610 mm |
| Required access area, width: | 965 mm |
| Required access area, height: | 1670 mm |
| Packaging dimension: | length |

| | |
|---|--|
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Nominal pressure (PN): | 10 |
| Pressure pipe connection (DN): | 65 |
| Pressure pipe connection (OD): | 75 mm |
| Distance pipe bottom outlet to tank bottom: | 1185 mm |
| Distance pipe bottom inlet to tank bottom: | 1255 mm |
| Outlet nominal size (OD): | 160 mm |
| Outlet nominal size (DN): | 150 mm |
| Inlet nominal size (OD): | 160 mm |
| Inlet nominal size (DN): | 150 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Coverage features | |
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | violet |
| Locking: | Quick-release closure |
| Tightness: | odour-tight |
| Wastewater contents | |
| Max. grease layer thickness: | 230 mm |
| Total volume: | 1880 l |
| Contents of sludge trap: | 1000 l |
| Storage quantity of grease: | 400 l |